


# King Vision®

## Video laryngoscope


### Quick Guide



Select blade type




**IMPORTANT**  
Always attach and remove the video adapter in unlocked position.




**aBlade only**

Slide on video adapter


- Decide which blade type to use depending on technique. Channeled blade or standard blade.
- Depending on which King Vision configuration is used attach blade directly or video adapter then aBlade.
- Connect blade to display before powering on
- No blade attached → no image; just static/snow (not applicable to aBlade configuration)
- Blade attached after display powered on → split image
- Blade disconnected from display → frozen image (for 20 sec) or auto shut off
- Note if display indicator turns red the display will turn off after approx. 15 minutes



Attach blade




Power ON




Test Battery & Image


- Lubricate blade and ETT keeping lubricant away from imaging sensor/camera window
- Channeled blade – Preload ETT into channeled if desired
- Standard blade – Install stylet in ETT and shape to match blade curve
- Power on and check for functional moving image
- Insert blade into mouth using mid-line approach; follow tongue and look for epiglottis. Don't go too deep



Insert



Intubate



Remove

- Place blade tip in vallecula and visualize vocal cords (for long floppy epiglottis, blade tip may need to be placed under the epiglottis)
- Advance and direct ETT through the vocal cords and to the proper depth in the trachea
- Stabilize/hold the ETT laterally while withdrawing blade from mouth



Select & Attach

- Disconnect blade from display; dispose of blade and clean/disinfect display
- If display becomes soiled with blood/secretions
- Clean with dampened wipes (enzymatic cleaning solution) for 4 minutes
- Disinfect with Sani-Cloth® wipes for 10 minutes replacing the wipes every 2 minutes
- Display is not submersible
- Do not expose opening for electrical connections on bottom of display stem to liquids
- Hold display upright when cleaning

